

## CM-6430



### FEATURES:

- A MPEG 1/2/4, JPEG and Motion JPEG Media Player
- LVDS I/F Support
- Support CF, IBM Microdrive, SM, SD, MMC, M.S., M.S. PRO, and xD
- Function as a USB 2.0 OTG
- Dual-Direction Copy Function (USB<-->Memory cards)
- Clock/Timer Function
- With optional memory capacity: 128MB, 256MB, 512MB, or 1GB
- Free firmware upgradeable from USB and memory cards

### SPECIFICATIONS:

<b>Description</b>	JPEG, Motion JPEG, MPEG-1, MPEG-2, and MPEG-4 Media Player
<b>Output Interface</b>	720p/1080i Progress or LVDS I/F
<b>Dimensions</b>	80 mm X 80 mm (3.15" X 3.15")
<b>System Environment</b>	1. NTSC/PAL LCD TV/Monitor 2. 15" above LCD Panel
<b>Operation Current</b>	<1A
<b>Operation Temperature</b>	0~70°C
<b>Storage Humidity</b>	10~90%
<b>Operation Humidity</b>	20~85%
<b>Power Supply</b>	DC 5V
<b>Standard Parts</b>	1. CM-6430 PCBA 2. DC 5V power adapter (Optional) 3. Infrared remote control (Optional)

**NOTE: Specifications are subject to change without notice. Brands and names are the property of their respective owners.**

**DATAFAB SYSTEMS INC. [www.datafab.com](http://www.datafab.com)**