

ECR32a-USB2G
Hi-Speed USB 32 in 1 Five-Slot Flash Card Reader/Writer



FEATURES:

- Support CF Type I, CF Type II, CF Ultra II, CF Extreme III, MicroDrive, SD, SD v1.1, SD v2.0, miniSD, MMC, MMC*plus*, MMC*mobile*, MMC*micro*, RSMAC, microSD, M.S., M.S. with Memory Select Function, MagicGate M.S., M.S. High Speed Data Transfer, M.S. Duo, MagicGate M.S. Duo, M.S. Duo High Speed Data Transfer, M. S. ROM, M.S. PRO, M.S. PRO High Speed, MagicGate M.S. PRO, M.S. PRO Duo High Speed, MagicGate M.S. PRO Duo, M2 (Memory Stick Micro), xD, xD Type M, and xD Type H
- True plug & play, and hot swapping
- View, edit, and copy photos/data/music
- USB 2.0 speed - Fast data/files access and transfer rate up to 480Mbps
- No driver is needed for WIN 2000/ME/XP, Mac 10x or above
- Compatible with PC & Mac

SPECIFICATIONS:

Description	Hi-Speed USB 32 in 1 Five-Slot Flash Card Reader/Writer
Dimensions	80 mm X 58 mm X 12 mm (3.15" X 2.28" X 0.47")
Weight	40g (1.41 ounce)
Interface	USB 2.0 (480 Mbps)
Power Supply	Bus-powered
System Environment	<ul style="list-style-type: none"> ● Operation Temperature: 0~70°C ● Storage Humidity: 0~90%RH ● Operation Humidity: 20~85%RH
System	<ul style="list-style-type: none"> ● Support Windows 2000 SP3/SP4, ME and XP

Requirements	<ul style="list-style-type: none"> ● Support Mac 8.6, 9.x, 10.1.2, and above (Driver is required for WIN 2000 and Mac 8.6/9.x.)
Standard Parts	<ul style="list-style-type: none"> ● One ECR32 unit ● External USB cable ● Quick start guide

NOTE:

This device carries three icons: one for Slot A&E, one for Slot D&C, and one for Slot B. Flash cards from either slot of sharing icon should not be inserted at the same time. For example, M2 (Slot A) & M.S. (Slot E) OR SD (Slot D) & microSD (Slot C) are not to be inserted simultaneously.

Specifications are subject to change without notice. Brands and names are the property of their respective owners.

DATAFAB SYSTEMS INC. www.datafab.com

