

**FA-CFIIxD**  
**xD-Picture Card™ CF Type II Adapter**



**Features**

FA-CFIIxD adapter is an intermediary of xD-Picture Card™ to CF interface devices. The FA-CFIIxD adapter converts xD cards to standard CompactFlash II format. CF-interface devices will have access to the latest xD devices, such as digital cameras, cellular phones, MP-3 players, and PDAs. It's truly plug & play. FA-CFIIxD is the gateway to a more diverse life style.

**Specifications**

<b>Dimensions</b>	42.8 mm x 36 mm x 3.3 mm
<b>Weight</b>	9g
<b>Interface</b>	CompactFlash
<b>Performance (Data Transfer Rate)</b>	Read: 900-950Kb/sec Write: 500-700Kb/sec
<b>Operation Voltage</b>	+5.0V ~ +3.0V (+/-5% wide range power supply)
<b>System Environment</b>	Operation Humidity: 20%-80% RH Operation Temperature: 0-40 °C
<b>System Requirements</b>	Support Windows 98SE, 2000, ME, and XP; Mac OS 8.6, 9.x, 10.1.2, and later

Note: Information in this material and specifications are subject to change without notice. Brands and names are the property of their respective brands.

**DataFab Systems Inc. [www.datafab.com](http://www.datafab.com)**